

MATERIAL SAFETY DATA SHEET

(COMPLIES WITH 29CFR 1910.1200)

SECTION I - CHEMICAL PRODUCT & COMPANY IDENTIFICATION

Identity (As Used on Label and List): Multi-Clean Clear Essence

Product Class: Water-borne floor polish

Emergency Telephone Number: 800-255-3924

Telephone Number for Information: 651-481-1900

Manufacturer's Name and Address:

Multi-Clean®, A Division of Minuteman International, Inc.

600 Cardigan Road

Shoreview, MN 55126

SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components (Specific Chemical Identity):

Chemical	Common Name(s)	%
A	Emulsified acrylic polymers (proprietary)	10 - 30
B	Diethylene glycol monoethyl ether CAS #111-90-0	3 - 7
C	Tributoxyethyl phosphate CAS #78-51-3	1 - 5
D	Emulsified polymer wax (proprietary)	1 - 5
E	Water CAS #7732-18-5	60 - 100

SECTION III - HAZARDS IDENTIFICATION

Emergency Overview

Appearance and Odor: Milky white liquid, mild acrylic odor

Primary Hazards: Irritant

Potential Health Hazards

Route(s) of Entry: Skin Absorption: X Ingestion: Inhalation: X

Eye: May cause irritation on contact.

Skin: May cause irritation on prolonged or repeated contact.

Ingestion: May be harmful if swallowed.

Inhalation: No effects expected.

Signs and Symptoms of Exposure: Irritation on direct contact.

Carcinogenicity: NTP? No IARC Monographs? No

OSHA Regulated? No

Target Organ (s): No additional data

Medical Conditions Generally Aggravated by Exposure: N. Av.

Health Hazards, Chronic: N. Av.

SECTION IV - FIRST AID MEASURES

Emergency and First Aid Procedures:

If Swallowed: Do not induce vomiting. Drink water in large amounts and call a physician immediately. Never give anything by mouth to an unconscious person. **Eye Contact:** Flush eyes with running water for at least 15 minutes. If irritation persists, obtain medical attention. **Skin Contact:** Flush thoroughly with cool water. Remove and wash contaminated clothing before reuse.

Sources Used: Raw material data, general toxicology from the trade for similar products.

SECTION V - FIRE FIGHTING MEASURES

Flammability: No **Autoignition Temperature:** N. Av.

Flash Point (method used): None

Flammable Limits: N. Av.

LEL UEL

Extinguishing Media: N. Av.

Water?

Foam?

Water Fog?

Alcohol Foam?

CO₂?

Dry Chemical?

Vaporizing Liquid?

Other?

Special Fire Fighting Procedures: N. Av.

Unusual Fire and Explosion Hazards: N. Av.

TDG Flammability Classification: Non-flammable

Sensitivity to Mechanical Impact: None

Sensitivity to Static Discharge: None

SECTION VI - ACCIDENTAL RELEASE MEASURES

Steps to be Taken in Case Material is Released or Spilled:

Dike and contain spill with inert material (sand, earth, etc). Collect spill with mop, absorbent material (example: floor-dri) or vacuum. Thoroughly rinse affected area with water.

SECTION VII - HANDLING AND STORAGE

Precautions to be Taken in Handling and Storing:

Storage Temperature: Minimum 40°F (4°C); Maximum 100°F (38°C)

Other Precautions: Keep out of reach of children. Keep from freezing.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory Protection (Specify Types): Not required

Ventilation: Local Exhaust: Not required

Special: Not required

Mechanical (General): Normal good ventilation sufficient.

Other: Not required

Protective Gloves: Natural rubber or synthetic.

Eye Protection: Approved safety goggles or glasses. **Footwear:** Not required

Other Protective Clothing or Equipment: Not required

Work/Hygienic Practices: Do not contaminate food or beverages with cleaning chemicals.

SECTION IX - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: Approximately 212°F

pH: 7 - 8

Specific Gravity (H₂O) = 1: 1.028

% Volatile: 80

Vapor Density (Air = 1): > 1

Odor Threshold: N. Av.

Evaporation Rate (Butyl Acetate = 1): N. Av.

Oil/Water Distribution Coefficient: N. Av.

Solubility in Water: Complete

Vapor Pressure (MM HG): N. Av.

Melting Point: N. Av.

SECTION X - STABILITY AND REACTIVITY

Stability: Unstable: Stable: X

Conditions to Avoid: N. Av.

Incompatibility (materials to avoid): N. Av.

Hazardous Decomposition or By-products: N. Av.

Hazardous Polymerization: May occur: Will not occur: X

Conditions to Avoid: N. Av.

SECTION XI - TOXICOLOGICAL INFORMATION

Chemical	OSHA PEL	ACGIH TLV	Recom.	LD50	LC50
A	None	None	N. Av.	N. Av.	N. Av.
B	N. Av.	N. Av.	N. Av.	5,000 mg/kg	> 200 mg/lL
C	None	None	N. Av.	N. Av.	N. Av.
D	None	None	N. Av.	N. Av.	N. Av.
E	None	None	N. Av.	N. Av.	N. Av.

Teratogen, Mutagen, Reproductive Toxin Status: No

Toxicologically Synergistic Products: N. Av.

SECTION XII - ECOLOGICAL INFORMATION

Ecotoxicological Information: N. Av.

Chemical Fate Information: N. Av.

SECTION XIII - DISPOSAL CONSIDERATIONS

Waste Disposal Method:

Dispose of spilled material in accordance with local, state and federal regulations. Waste from normal product use (according to manufacturer's directions) may be sewerred in compliance with local, state and federal regulations.

RCRA Hazard Class: None

SECTION XIV - TRANSPORT INFORMATION

Shipping Classification: Buffing or polishing compound

UN Number: N. Av.

Packing Group: N. Av.

SECTION XV - PREPARATION DATA

Prepared By: Mike Tarvin

Telephone Number: 651-481-1900

Date: 5-09

SECTION XVI - REGULATORY INFORMATION

US Federal Regulations

TSCA Status: All ingredients listed.

CERCLA Reportable Quality: None

SARA Title III

Section 302 Extremely Hazardous Chemicals: None

Section 311/312 Hazard Category: Immediate health hazard

Section 313 Toxic Chemicals: Diethylene glycol monoethyl ether (glycol ether).

State Regulations

International Regulations

WHMIS Controlled Product Hazard Class: D, 2B

SECTION XVII - OTHER INFORMATION

None

N. Av. - Not Applicable; N. Av. - Not Available

NFPA SYSTEM

1 A. Health Hazard 0 A. Fire Hazard 0 A. Reactivity Hazard

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE, HOWEVER NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. MINUTEMAN INTERNATIONAL, INC. ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF THE MATERIAL.